MIRAI
by chimei

32
81cm

DTL-632E500
LCD TV

WWW.MIRAI.EU

HD ready

ChroMAX circuitry

HDMI

1366 x768 WXGA

6.5 ms Ultra Fast

500 nits Luminance

1500:1 Contrast

3 YEAR WARRANTY - 3 YEAR WARRANTY -

...experience the future

Jupiterstraat 82 • 2132 HE Hoofddorp • The Netherlands
Email: info@chimei.eu • Tel: +31 (0)23 - 565 6930 • Fax: +31 (0)23 - 565 6931
www.mirai.eu

MIRAI
by chimei

32 81cm DTL-632E500 LCD TV

Screen Size	697.6845(H) x 392.256(V)mm
Aspect Ratio	16 : 9
Pixel Pitch	1.53225 (H) x 1.53225 (V)mm
Panel Resolution	1366 x 768
Brightness	500 cd/m²
Contrast Ratio (typ.)	1500 : 1
Response Time (typ.)	6.5 ms
Viewing Angles (typ.)	176º(H) / 176º(V)
Standard TV	B/G, D/K, I, L/L=
Tuner System	PAL, SECAM
Display Color	16.7 M
Control Panel	Power(On/Off), Source Select(TV/SCART 1/SCART 1-S/SCART 2/YPbPr/ VGA/HDMI), Menu(OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: SRGB/SV/AV(In), TV (Out) SCART 2: SRGB/AV (In), TV/AV (Out) YPbPr (In)/VGA, PC Audio In (for VGA)/HDMI (In), Headphone (Out), Audio Out (R/L)
Support Timing	480i, 480p, 576i, 576p, HDTV 720p, 1080i
Speaker	10W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Colour Temp, Picture Mode, Aspect Ratio, Auto (picture setup), Clock, Phase, H-Position, V-Position, CH Scan, Program, Manual Scan, Program Edit, Audio (Balance, Bass, Treble, Surround), Language
Pic-Mode	Vivid / Movie / Sport / Game / User
Aspect Ratio	Full / Zoom1 / Zoom2 / Original
Teletext	250 pages
Power Supply	AC 100-240 V, 50/60Hz
Power Consumption	< 180W, Standby < 1W
Safety / EMC	CB, Intertek-GS / CE / RoHS, WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord
VESA mounting	100 x 200mm
System Dimension	804(W) x 580(H) x 224(T) mm
N.W.	12.5 kg

...experience the future

E & O, E
Pixel policy in accordance with ISO 13406-2

Jupiterstraat 82 • 2132 HE Hoofddorp • The Netherlands
Email: info@chimei.eu • Tel: +31 (0)23 - 565 6930 • Fax: +31 (0)23 - 565 6931
www.mirai.eu

WWW.MIRAI.EU